



LANDFILL WASTE ACCEPTANCE PROTOCOL 2024

Out of Region



Introduction

The Southern Regional Out of Region Landfill Waste Acceptance Protocol provides the following information.

- Classification and definition of the types of waste
- Waste Type Disposal Protocols
- Testing Requirements
- FAQ
- 2023/2024 Financial Year - Out of Region Pricing
- Waste Acceptance Schematic
- AB Lime Class 1 Landfill Waste Acceptance Criteria.

Classification and definition of the types of waste

Permitted Waste

Permitted Waste – Accepted at the Southern Regional Landfill

Permitted waste is defined as Municipal Solid Waste. Municipal Solid Waste is any non-hazardous, solid waste from a domestic, commercial or industrial source that does not fall within the categories of Special Waste or Excluded Waste as those terms as defined in this Waste Acceptance Protocol.

Municipal Solid Waste may contain small amounts of Special Waste but cannot exceed what would be typically seen in general municipal waste throughout New Zealand that is accepted to landfill. For example what would be found in a curb side general waste bin.

Special Waste

Special Waste – Accepted at the Southern Regional Landfill with disposal conditions and a Special Waste Permit

Special Waste is waste that is non-hazardous waste and some accepted hazardous wastes set out in this Waste Acceptance Protocol that requires special handling and disposal activities at the landfill. For example, putrescible waste must be delivered in sealed containers and may need to be deposited directly into an excavation, prepared prior to its arrival and covered immediately after deposit. Deodorants and lime may also be required.

Special Waste is:

- putrescible waste from commercial or industrial sources, such as produce, fish or animal waste
- Sludge, such as septage, water or wastewater treatment plant sludge, mud tank waste, grease trap waste – must have at least 20% solids content
- Contaminated Soils – requires test results as limits apply
- Contaminated Material – requires test results as limits apply
- Accepted Hazardous wastes which are outlined in this Waste Acceptance Protocol
- Any other waste agreed by the Southern Regional Landfill to be Special Waste.
- Tyres – Car, truck, and tractor.

All Special Waste, apart from tyres, must have a Special Waste Permit issued by the Southern Regional Landfill. The procedure for applying for a Special Waste permit can be seen in the Special Waste Procedure section of this protocol.

Accepted Hazardous Waste – Accepted at the Southern Regional Landfill with disposal conditions and a Special Waste Permit

The Southern Regional Landfill can accept Accepted Hazardous Waste with disposal conditions and a Special Waste Permit. These wastes include:

- Asbestos waste
- Methamphetamine contaminated waste – requires test results as limits apply
- Medical Waste in accordance with NZS 4304:2002.

Accepted Hazardous Waste must have a Special Waste Permit issued by the Southern Regional Landfill. The procedure for applying for a Special Waste Permit can be seen in the Waste Tye Disposal Protocols – Special Waste.

Controlled Waste – Accepted at the Southern Regional Landfill with disposal conditions.

Controlled Waste is Special Waste that does not require a Special Waste Permit and is not suitable to go to a composting facility. Waste types include:

- Woody waste
- Odorous greenwaste.

Prohibited Wastes

Excluded Waste – Not accepted at the Southern Regional Landfill

Excluded Waste is waste that can be readily processed into other classes of waste for which there are readily available, alternative methods of disposal, or is waste that can be readily processed into a resource material.

Excluded waste includes but is not limited to:

- **Bulky recyclable materials** – i.e. car bodies, large scrap metal, car batteries and lithium batteries. Whiteware, baille and silage wrap, other bulk recyclable material which include bales of soft plastic or glass bottles in bulk.
- **Large loads of greenwaste** – i.e. vegetative material such as lawn clippings, hedge trimmings, trees, leaves.
- **Large loads of unsorted demolition waste** – i.e. solid waste resulting from the demolition, erection, construction, refurbishment, or alteration of large scale operations on buildings or from the construction, repair or alteration of infrastructure-type development such as roads, bridges, dams, tunnels, railways and airports.

Unsorted demolition waste – comprises material that is suitable for disposal at a cleanfill site and/or material that can be recycled or repurposed.

Sorted demolition waste – can come to the Southern Regional Landfill which has all waste that is suitable for disposal at a cleanfill site and all waste that can be recycled or repurposed, removed.

If any of these wastes are deemed not suitable for sorting or processing, Excluded Waste can be disposed of at the Southern Regional Landfill with direction from Environment Southland.

Hazardous Waste – Not accepted to the Southern Regional Landfill

With the exception of the Accepted Hazardous Waste no hazardous waste is accepted for disposal at the Southern Regional Landfill. Hazardous wastes are those defined in the Hazardous Substances and New Organisms Act 1996.

These include:

- Wastes which are explosive, flammable, oxidising, or corrosive, or which are identified as possessing these characteristics in the HSNO regulations
- Wastes capable by any means after disposal of yielding another material for example leachate which possesses any of the above characteristics
- Waste which exhibits the characteristics of toxicity and eco-toxicity, which following testing using the USEPA toxicity characteristic leaching procedure (TCLP) result in leachable concentrations of contaminants in excess of the leachable concentration limits listed in Schedule 2 – Class 1 landfill acceptance criteria which can be seen in this Waste Acceptance Protocol.
- Wastes which exhibit the characteristics of toxicity and eco-toxicity with total concentrations in excess of the total concentration limits listed in Schedule 2-Class 1 landfill acceptance criteria which can be seen in this Waste Acceptance Protocol
- Wastes that contain substances that are persistent, bio accumulative and toxic, except as provided for in Schedule 2 – Class 1 landfill acceptance criteria. These substances are subject to the Stockholm Convention and various regulations. The definition of persistent bio accumulative and toxic compound is any compound that meets the criteria as defined in Annex D of the Stockholm Convention obvious examples include the pollutants found in firefighting foams.
- Wastes which are radioactive and controlled under the Radiation Safety Act 2016. For avoidance of doubt this does not apply to incidental radioactive material that is reasonably expected to be contained within the Municipal Waste Stream such as smoke detectors.

The definition of “Hazardous Waste” does not include small quantities of waste products containing potentially hazardous components that are likely to have adverse effects on the environment, such as can be expected to be contained in the municipal waste stream.

Other Prohibited Waste - not accepted to the Southern Regional Landfill

- Hazardous Medical wastes
- Sludges with less than 20% solids
- Non-compliant waste – i.e. waste that is delivered breaching conditions set out in its Special Waste Permit
- Liquid Waste
- Offensively odorous waste – odorous wastes require pre-treatment which is detailed in that wastes Special Waste Permit.

Waste Type Disposal Protocols

Permitted Waste

1. Can come directly to landfill with permission from Southern Regional Landfill. Email all enquiries to waste@ablime.co.nz
2. Must be carted by an Authorised User. A current list of authorised users can be requested from the Waste team by emailing waste@ablime.co.nz. If you are a registered transport or contracting company which has vehicles suitable for transporting waste and would like to become an authorised user, please email waste@ablime.co.nz.
3. Waste loads must be covered, and all drivers need to be inducted to enter the Southern Regional Landfill site. Inductions can be done online. Please contact munahi@ablime.co.nz regarding becoming inducted.
4. Pricing can be seen under the Out of Region Pricing section in this Waste Acceptance protocol under Permitted Waste. Please note pricing is only valid to the financial year the Waste Acceptance Protocol is published. Contact Southern Regional Landfill for the latest Waste Acceptance Protocol.

Special Waste

1. Needs to be approved by the Southern Regional Landfill for disposal. Contact the Southern Regional Landfill Waste team at waste@ablime.co.nz. Give as much detail regarding the waste as possible and its location. Send through TCLP test results if available and required.
2. Southern Regional Landfill may come back asking for more information or request TCLP or relevant testing to be carried out.
3. If the waste is acceptable to come to landfill, Southern Regional Landfill will detail disposal conditions for the waste i.e., only 1 truck and trailer load a day or odour neutralising spray to be applied before transportation.
4. Acceptable Special Waste now needs a Special Waste Permit. The owner of the waste should apply for the Special Waste Permit.
5. Apply for a Special Waste Permit by requesting an application form from Southern Regional Landfill at waste@ablime.co.nz - include as much information as possible in the permit application page and attached test results if relevant.
6. Send back a completed Special Waste Permit to waste@ablime.co.nz.
7. Special waste must be carted by an Authorised User. Please note that not all authorised users may be able to cart your special waste as their transport vehicles may not be suitable. It is recommended contacting authorised users regarding the waste before applying for a permit. A current list of authorised users can be requested from the Waste team by emailing waste@ablime.co.nz. If you are a registered transport or contracting company which has vehicles suitable for transporting waste and would like to become an authorised user, please email waste@ablime.co.nz.
8. Once a permit is granted, take note of the disposal conditions as these need to be adhered to including your Authorised User for your transport. If waste turns up for disposal in a condition that breaches any information detailed on the permit it will be turned away.
9. Give a copy of the Special Waste permit to the Authorised User as they need to also adhere to the conditions of disposal.
10. Special waste needs at least 48 hours' notice before it comes to the Southern Regional Landfill. The transport operator or permit holder can book in by emailing weighbridge@ablime.co.nz or calling **03-236-1492**. This is important because every day special waste locations are planned and GPS located. Special waste often requires disposal actions such as immediate burial or blending with lime onsite therefore staff need to be prepared to accept the special waste load. If a special waste load turns up without a booking, it will be sent away.
11. All Special Wastes need to arrive at the Southern Regional Landfill covered and in sealed bins i.e. No waste can leak or be blown onto public roads. All drivers need to be inducted. Inductions can be done online. Please contact munahi@ablime.co.nz regarding becoming inducted.
12. Pricing can be seen under the Out of Region Pricing section in this Waste Acceptance protocol under Special Waste. Please note pricing is only valid to the financial year the Waste Acceptance Protocol is published. Contact Southern Regional Landfill for the latest Waste Acceptance Protocol. This pricing does not include any other costs associated with the waste such as meeting conditions in the permit – i.e. lime is blended through sludges for stabilisation onsite therefore there is a cost per tonne of lime. Southern Regional Landfill will detail all expenses regarding conditions to the waste owner before the permit is applied for.
13. Burial certificates can be issued if required. Email the waste team at waste@ablime.co.nz

Tyres

1. Tyres are considered a special waste but do not require a Special Waste Permit
2. Tyres need to be approved by the Southern Regional Landfill for disposal. Contact the Southern Regional Landfill Waste team at waste@ablime.co.nz to notify about a tyre waste load. Include detail on the type of tyres and amount.
3. Must be carted by an Authorised User. A current list of authorised users can be requested from the Waste team by emailing waste@ablime.co.nz If you are a registered transport or contracting company which has vehicles suitable for transporting waste and would like to become an authorised user, please email waste@ablime.co.nz.
4. Must be booked in with at least 48hrs notice. This is important because tyres are processed by cutting down onsite before disposal to the landfill. The transport operator or permit holder can book in by emailing weighbridge@ablime.co.nz or calling 03-236-1492.
5. Waste loads must be covered, and all drivers need to be inducted to enter the Southern Regional Landfill Site. Inductions can be done online. Please contact munahi@ablime.co.nz regarding becoming inducted.
6. Tyres have both a per tyre price and a total tonnage price. This is because of the processing of cutting up each tyre onsite. Pricing can be seen under the Out of Region Pricing section in this Waste Acceptance protocol under Tyres. Please note pricing is only valid to the financial year the Waste Acceptance Protocol is published. Contact Southern Regional Landfill for the latest Waste Acceptance Protocol.

Acceptable Hazardous Waste

The same process and pricing applies for Acceptable Hazardous Waste as Special Waste, however each Acceptable Hazardous Waste has its own extra disposal conditions.

Methamphetamine Contaminated Waste

- Acceptable contaminated material includes wall linings including gib board, soft furnishings i.e. curtains, carpets, furniture, bedding, clothing and whiteware.
- NOT accepted contaminated material include actual stocks of chemicals used in, or left over from methamphetamine manufacturing.
- Test results are required, and methamphetamine contaminated waste can only be accepted to landfill if the level of contamination is less than 100µg/100cm². Send test results through to waste@ablime.co.nz and a member of the waste team will be in touch regarding acceptance.
- If test results fall outside of the acceptable limit above then the waste will need approval from Environment Southland to be considered for disposal

Asbestos Waste

- Asbestos waste must be disposed of in accordance with Health and Safety at work (asbestos) regulations 2016. This includes the responsibilities of Southern Regional Landfill, the waste owner and waste transporter.
- Asbestos does not need test results if it is known that asbestos is present. Test results are required if there is uncertainty around presence.
- There are 2 types of asbestos waste loads – “Discrete Loads” such as asbestos contaminated building material and “Bulk Rubble” such as asbestos contaminated soil. Both have different disposal conditions:



- a) **Discrete Loads** – must be wetted down if appropriate then placed onto a pallet and double wrapped with pallet wrap. It must be identified with asbestos hazardous substance stickers. An example of the type of stickers used can be seen below and can be purchased from safety stores.
- b) **Bulk Rubble** – The truck and trailer units must be plastic sheet lined. The plastic sheeting needs to be folded over top of the loads and then appropriately labelled with asbestos hazardous substance stickers. An example of the type of stickers used can be seen below and can be purchased from safety stores. The load must be wetted down at the point of loading and prior to travel to suppress any dust generation but not come to the landfill drenched.

Medical Waste

Accepted medical wastes are detailed in accordance with NZS 4304:2002 “Health Care Waste Management”.

Controlled Waste

- Controlled waste has the same pricing as Special Waste
- The same Special Waste disposal protocols apply.
- It is expected that any odorous green waste is treated to suppress or minimise odour
- Controlled Waste needs at least 48 hours' notice before it comes to the landfill. The transport operator or permit holder can book in by emailing weighbridge@ablime.co.nz or calling **03-236-1492**. This is important because every day Special Waste locations are planned and GPS located. Special waste often requires disposal actions such as immediate burial or blending with lime onsite therefore staff need to be prepared to accept the special waste load. If a special waste load turns up without a booking, it will be sent away.

Testing Requirements

Testing is required but not limited to the following Special Waste and Acceptable Hazardous Waste

- Any new waste stream to be disposed of at the Southern Regional Landfill that Southern Regional sees potential risk to harbouring potential contaminants and effecting leachate composition onsite
- Any material suspected to be possibly contaminated
- Contaminated soils
- Material that has been part of an industrial process and has the potential to be contaminated from the process for example materials from a tanalised timber yard may be contaminated with copper
- Any material that is contaminated with a substance noted in the “Waste Acceptance Criteria” which can be seen at the end of this protocol
- Historical landfills
- Any material coming from a HAIL site.

Suitable testing include:

- Screening
- TCLP testing – Toxicity Characteristic Leaching Procedure – secondary testing after screening, if screening results return outside of our Waste Acceptance Criteria we will request TCLP testing to be carried out on those exceeding contaminants only.
- ASLP Testing - Australian Standard Leaching Protocol – for PFAS contaminated material ONLY
- Screen testing for Methamphetamine contaminated materials
- Presence/absence testing for asbestos. If uncertain of presence

If there is uncertainty around testing Southern Regional Landfill will give direction on what testing is required for the particular waste to be considered for disposal. Email all information regarding the waste to waste@ablime.co.nz.

Once test results have been issued, they need to be sent through to the Southern Regional Landfill Waste team at waste@ablime.co.nz. Southern Regional Landfill will assess the test results and make a decision on acceptance.

Southern Regional Landfill's “Class 1 Landfill Waste Acceptance Criteria” can be seen at the end of this Waste Acceptance Protocol. All contaminated waste must fall within the limits of the contaminants outlined in these criteria to be eligible for acceptance at the landfill. Southern Regional Landfill makes the final decision whether to accept a waste even if it does fall within the acceptable limits – i.e., too many of one type of contaminated waste in a short time frame may lead to waste not being accepted even though it falls within acceptance criteria limits.

If limits fall outside Southern Regional Landfill’s Waste Acceptance Criteria and a waste owner wishes to carry on with gaining acceptance, treatment or encapsulation of a material can be investigated. A contamination specialist will be required to carry this out.

FAQ

I'm unsure about what category my waste falls into and if it can be accepted at the Southern Regional Landfill?

If you are unsure what category your waste fall into or if the Southern Regional Landfill accepts the waste in the first instance please check the "Waste Acceptance Schematic" found at the end of this report. If there is still uncertainty, then get in touch with the waste team at Southern Regional by emailing waste@ablime.co.nz. Provide as much detail regarding the waste as possible and its location. Photos are also helpful.

I have a waste that is located in the Southland region, does the same Waste Acceptance Protocol apply?

Waste within Southland and out of region have separate Waste Acceptance Protocols, please email waste@ablime.co.nz for the "Southland Waste Acceptance Protocol".

What if I want to use a transport operator or are a transport operator which is not on the authorised users list?

If you are a transport operator, which is a registered company and has appropriate vehicles to transport waste, you can apply to become an authorised user of the landfill. To begin this process, get in touch with the waste team at waste@ablime.co.nz

I am a member of the public; can I bring my trailer load of waste to the landfill?

No. The landfill is not open to the public. You will need to take the trailer load of waste to your nearest transfer station.

I have some contaminated material that exceeds the acceptable limits listed in your waste acceptance criteria, is there no way this can go to landfill?

If a waste is too high in contaminants under the waste acceptance criteria limits then there may be suitable options so it can come to landfill by treating the waste. Treatment options may include but not limited to blending with another product to stabilise the waste and re-testing to assess effectiveness or encapsulating the waste in concrete. It is recommended that third-party advice is sort to carry testing out on the best options such as a contamination consultant. Southern Regional Landfill can give some advice on what to do with a waste that exceeds the waste acceptance criteria limits.

Where does "Out of Region" cover?

When stating "Out of Region" this refers to anywhere outside of the following council areas:

- Southland District Council
- Invercargill City Council
- Gore City Council.

Why should the waste owner apply for a Special Waste Permit can't the transport operator do this?


It is recommended that the waste owner applies for the Special Waste Permit as this ensures all responsibility falls back onto the waste owner. If you are not the waste owner, and you apply for a Special Waste Permit for the waste then you become responsible for the waste. For example, if waste arrives at Southern Regional Landfill in an unacceptable condition it is the Special Waste Permit holders responsibility to bring the waste up to standard or if an extra charge occurs due to unexpected mitigation onsite then the Special waste Permit holder is the one who is charged. If the transport operator wants to take full responsibility for the waste, then they can do this.

2023 Financial Year Out of Region Pricing

Description	Unity	Rate Per Unit \$ (GST Exclusive)
Permitted Waste	Tonne	\$193.97
Special Waste	Tonne	\$308.22
<i>Other Special Waste:</i>		
Truck and Tractor Tyres	Each	\$9.91 plus weight
Car & 4x4 Tyres	Each	\$3.16 plus weight

Prices exclude any costs associated with meeting the conditions of a Special Waste Permit. For example potentially odorous wastes including putrescible wastes and Biosolids require lime to be added at the landfill for stabilisation and this incurs an extra charge for the tonnage of lime used. All pricing will be communicated by Southern Regional Landfill to the waste owner before a contract to accept waste is signed

Waste Acceptance Schematic



Key



= Accepted at Landfill



= Accepted at Landfill with conditions. Some conditions may include testing results, odour control and Special Waste Permits. All need to be booked in for delivery 48hrs in advance.



= Not accepted at Landfill

The items listed are examples only. Any item not listed please refer to the Waste Acceptance Protocol

Attachment 1: Schedule 2

Schedule 2 is relevant to Condition 21 of the Solid Waste to Land Discharge Permit

Class 1 Landfill Waste Acceptance Criteria

For Class 1 landfills, leachability testing should be completed to provide assurance that waste materials meet the following recommended waste acceptance criteria. The waste acceptance criteria leachability limits represent maximum values which should not be exceeded and should be viewed as a minimum treatment specification for a landfill.

If the following limits are exceeded by a leachate extract of the waste with respect to any of the listed constituents, then the material is not suitable for disposal to the facility.

Table D-1 Class 1 Waste Acceptance Criteria for Inorganic and Organic Elements³

Contaminant of concern	Unit	Maximum allowable TCLP concentration
Arsenic	mg/L	5
Barium	mg/L	100
Benzene	mg/L	0.5
Cadmium	mg/L	1
Carbon Tetrachloride	mg/L	0.5
Chlordane	mg/L	0.03
Chlorobenzene	mg/L	100
Chloroform	mg/L	6
Chromium	mg/L	5
Endrin	mg/L	0.02
m-Cresol	mg/L	200
o-Cresol	mg/L	200
p-Cresol	mg/L	200
Total cresol	mg/L	200
1,4-Dichlorobenzene	mg/L	7.5
1,2-Dichloroethane	mg/L	0.5
1,1-Dichloroethylene	mg/L	0.7
2,4-Dinitrotoluene	mg/L	0.13
2,4-Dichlorophenoxyacetic acid	mg/L	10
Heptachlor	mg/L	0.008
Hexachloro – 1,3-butadiene	mg/L	0.5
Hexachlorobenzene	mg/L	0.13
Hexachloroethane	mg/L	3
Lead	mg/L	5
Lindane	mg/L	0.4

³ US EPA Chapter 40 CFR

Contaminant of concern	Unit	Maximum allowable TCLP concentration
Mercury	mg/L	0.2
Methoxychlor	mg/L	10
Methyl ethyl ketone	mg/L	200
Nitrobenzene	mg/L	2
Pentachlorophenol	mg/L	100
Pyridine	mg/L	5
Selenium	mg/L	1
Silver	mg/L	5
Tetrachloroethylene	mg/L	0.7
Toxaphene	mg/L	0.5
Trichloroethylene	mg/L	0.7
2,4,5-Trichlorophenol	mg/L	400
2,4,5-Trichlorophenoxypropionic acid 1	mg/L	1
2,4,6-Trichlorophenol	mg/L	2
Vinyl chloride	mg/L	0.2
Sulfides	ppm	50
Cyanides	ppm	50
Total halogenated compounds	ppm	1,000
Total synthetic non-halogenated compounds	ppm	10,000
Polychlorinated biphenyls	ppm	50

Table D-2 Class 1 Waste Acceptance Criteria for Inorganic and Organic Elements⁴

Contaminant of concern	Unit	Maximum allowable TCLP concentration
Aluminium	ppm	40
Aniline	ppm	0.2
Antimony	ppm	0.6
Beryllium	ppm	10
Boron	ppm	20
Bromodichloromethane	ppm	1
Bromoform	ppm	10
Carbon disulphide	ppm	3
2 Chlorophenol	ppm	0.05
Copper	ppm	5.0
1,2 Dibromo-3-chloropropane	ppm	0.2
Dibromochloromethane	ppm	10

⁴ Module 2: Hazardous Waste Guidelines MfE 2004

Contaminant of concern	Unit	Maximum allowable TCLP concentration
1,2 Dichlorobenzene	ppm	0.2
1,2 Dichloroethene	ppm	10
Dichloromethane	ppm	2
2,4 Dichlorophenol	ppm	0.05
1,2 Dichloropropane	ppm	1
1,3 Dichloropropene	ppm	2
Diethylphthalate	ppm	100
Dimethylphthalate	ppm	400
Ethyl benzene	ppm	50
Fluoride	ppm	200
Lithium	ppm	20
Molybdenum	ppm	10
Naphthalene	ppm	10
Nickel	ppm	10
Phenol	ppm	40
1,1,1,2 Tetrachloroethane	ppm	50
Tin	ppm	1000
Toluene	ppm	100
Tributyltin oxide (TBTO)	ppm	3
1,1,1 Trichloroethane	ppm	200
1,1,2 Trichloroethane	ppm	500
Vanadium	ppm	2.0
Xylene (m,o,p)	ppm	100
Zinc	ppm	10.0

Table D-3 Waste Acceptance Criteria incorporated due to at least Annual Review

Date Added	Contaminant of Concern	Concentration Type	Landfill Acceptance Criteria	Comments
March 2023	Sum of PFOS + PFHxS ¹	ASLP leachable concentration (µg/L)	7 µg/L	Drinking water x 100 (Department of Health 2017)
		Total Concentration	50mg/kg ²	Soil – Human health industrial/commercial x 100 Total concentration for PFOS + PFHxS and PFOA (including related substances) of 50 mg/kg based on the low content

¹ Where the criteria refer to the sum of PFOS and PFHxS, this includes PFOS only, PFHxS only and the sum of the two

² Waste concentrations must be less than both the relevant leachable concentration and the total concentration values. Where significant PFAS are present beyond PFOS, PFHxS and PFOA, these solid PFAS-contaminated materials may not be acceptable for landfill disposal. This should be discussed on a case by case basis with the Independent Management Plan Reviewer(s) and Environment Southland.

Date Added	Contaminant of Concern	Concentration Type	Landfill Acceptance Criteria	Comments
				limit
March 2023	PFOA	ASLP leachable concentration (µg/L)	56 µg/L	Drinking water x 100 (Department of Health 2017)
		Total Concentration	50mg/kg	Soil – Human health industrial/commercial x 100 Total concentration for PFOS + PFHxS and PFOA (including related substances) of 50 mg/kg based on the low content limit